

# Digi-Wave™ DLT-100

## NEW FEATURES

### Set-Up Lock (SLOC)

Power on the DLT-100 

Set-up Lock enables the Administrator to prevent unauthorized changes to the system set-up.

**NOTE: Each DLT-100 has to be locked and unlocked individually.**

To activate SLOC:

Press the yes key  twice, then the no key  twice (YES-YES-NO-NO). This has to be done within 2 seconds. 'SLOC' will appear momentarily on the screen. SLOC is now enabled.

When SLOC is enabled, if a user tries to change any setting by entering the set-up mode, 'SLOC' will appear momentarily on the screen. See figure 1.

To unlock this feature, the same YES-YES-NO-NO sequence must be entered. There will be no prompt showing that SLOC was disabled. Accessing the set-up mode is the indication that SLOC is disabled.

Figure 1



### Tone Control

Power on the DLT-100 

Press and hold the - and + buttons simultaneously for 2 seconds  

The LCD will display the last tone setting t: (1 - 9)

Using the -/+ buttons, adjust the tone up or down  

1 = Most bass response

5 = Flat (Default)

9 = Most treble response

Press and hold the - and + buttons simultaneously for two seconds to save the tone setting  

Figure 2



### Programming Secure Key Code

Entering a four digit **Secure Key Code** into each group members's DLT-100, prevents unauthorized individuals from listening in on the group.

1. Decide on a four digit numerical code that you will enter into each DLT, i.e. 1357. You must use the same code on each DLT in the group.
2. Start with the Chairman Master when programming.
3. With the DLT-100 turned on, hold the no and yes buttons   simultaneously for two seconds to enter the set-up menu.
4. Use the menu button  to scroll through the menu pages until you get to the screen displayed in figure 3.
5. The first dash will be blinking; using the   button, insert the first digit of the code (0 - 9).
6. Press the menu button  again to move to the second dash which will now be blinking.
7. Enter the next digit and continue until all four digits have been entered.
8. One more press of the menu button  and you will see the word Code displayed (figure 4).
9. With the Secure Key Code entered, exit the set-up menu by holding the no/yes buttons simultaneously for two seconds.
10. Follow the same process with the Chairman Slave and Slave units.

Figure 3




Figure 4



**NOTE: There will be fewer pages to scroll through on the Chairman Slave and Slave units to get to the code set-up screen.**