

# PROLOOP FSM plus

## Magnetic Field Strength Measuring Device



The new PROLOOP FSM plus is a measuring device that measures the magnetic field strength of induction loop systems according to IEC 60118-4:2006 and BS 6083, Para. 4. The device is designed for professional use and delivers reliable RMS values on the output level, response frequency, AGC function (Automatic Gain Control), distortion and background noise in the tested induction loop. In addition, it enables the user to make an acoustic evaluation of the sound via earphones.

- Conforms to IEC 60118-4: 2006 standard
- Adjustment possibilities for two test ranges:
  - background noise
  - field strength
- RMS-measuring range calibrated to 400mA/m = 0dB
- Multi-colored LEDs for excellent legibility
- LED-scale with 1dB resolution
- 3.5 mm stereo headphone jack with volume control
- Handy, light-weight, rugged chassis
- Switchable A weighted filter

<b>True RMS:</b>	125 ms average time
<b>Measuring range:</b>	+6 dB -40 dB (0 dB = 400mA/m)
<b>Power supply:</b>	2x 1.5V AA batteries
<b>Display:</b>	LED Battery status control
<b>Field strength:</b>	LED-Scale (1dB resolution)
<b>Output:</b>	3.5 mm stereo headphone jack with volume control
<b>Dimensions:</b>	3.3" x 5" x 1.4" (83 x 126 x 35 mm)
<b>Weight:</b>	6.0 oz. (170 g) (incl. batteries)
<b>Warranty:</b>	2 years

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

**Domestic Sales**

Williams AV  
 10300 Valley View Rd  
 Eden Prairie, MN 55344  
 Ph: 800-328-6190 / 952-943-2252  
 FAX: 952-943-2174  
 Email: info@williamsav.com  
 Web: www.williamsav.com

**International Sales**

International Sales Department  
 Williams AV  
 10300 Valley View Rd  
 Eden Prairie, MN 55344 USA  
 Phone: +1 952 943 2252  
 Fax: +1 952 943 2174  
 Email: info@williamsav.com  
 Web: www.williamsav.com

**WILLIAMS AV**  
 info@williamsav.com / www.williamsav.com  
 800-843-3544 / INTL: +1-952-943-2252