

Production Intercom • High Noise Environments • Live Sound Stage • Factory Tours • Military Training

# PLW 014

## POWER LOOP WIRE 14 GA



Power loop wire, 14 ga, 500 ft (152.4 m) spool, black.

### Industry Approvals

- CSA Spec. C22.2, No. 127
- UL Spec. AWM Style 1015, 1019, 1020, 1230, 1284, 1032, 1283, 1232, 1028
- CSA LL90458
- UL E30398
- Meets material content restrictions of the RoHS-2 Directive

### PLW 014

Wire Type	Stranded bare copper
Insulation Type	Thermoplastic insulation
Length	500ft (152.4 m)
Spool Dimensions	6.5"W
Spool Weight	9.8 lbs
Color/Material	Black
Max. Temperature Exposure	105°C Dry
Rating	600 Volt
Conductor Size (AWG)	14
Number of Strands	41
Nominal Insulation Thickness	0.030 in. (0.76 mm)
Nominal Overall Diameter	0.136 in (3.45 mm)
Net Weight	4.2 kg (9.15 lbs)
Approvals	RoHS

### Domestic Sales

Williams AV  
 10300 Valley View Rd  
 Eden Prairie, MN 55344  
 Ph: 800-328-6190 / 952-943-2252  
 FAX: 952-943-2174  
 Email: [info@williamsav.com](mailto:info@williamsav.com)  
 Web: [www.williamsav.com](http://www.williamsav.com)

### International Sales

International Sales Department  
 Williams AV  
 10300 Valley View Rd  
 Eden Prairie, MN 55344 USA  
 Phone: +1 952 943 2252  
 Fax: +1 952 943 2174  
 Email: [info@williamsav.com](mailto:info@williamsav.com)  
 Web: [www.williamsav.com](http://www.williamsav.com)



[info@williamsav.com](mailto:info@williamsav.com) / [www.williamsav.com](http://www.williamsav.com)  
 800-843-3544 / INTL: +1-952-943-2252