

# Convey Video

AI-POWERED, REAL-TIME VIDEO TRANSLATION



With advances in technology and the ability to travel, our communities and business opportunities have become more diverse. These diverse living and working environment have strengthened our societies, yet language barriers often make it difficult to create inclusive environments for engagement and understanding.

Convey Video breaks-down communication barriers and makes inclusion easier with real-time, speech-to-text translation. Through the power of artificial intelligence (AI), it can translate audio up to 109+ languages and 153 dialects. Live-translated subtitles can overlay on any video source or be keyed onto an external source.

Studies have shown that individuals feel more valued when they are communicated to in their native language. Individuals' comprehension and understanding also increase when communicated to in their native language.

Convey Video is affordable and easily integrated into an array of video environments, making it easier to expand access to language translation for a wider range of events.

## Key Features

- Selectable video input options.
- Output via HDMI, USB, or text over black for keying onto another source
- Capture and translate audio via HDMI, USB or XLR
- A profanity filter can be turned on or off to adjust to the requirements of the specific situation.
- Archiving including capture audio input [MP3], video output with translations/captions [MP4], text captions [.txt] and translated text [.txt].
- ASIO driver increases compatibility with common DSP audio input sources

## Applications

- Presentations
- Language interpretation
- Video Conferencing

## Markets

- Houses of Worship
- Healthcare - medical centers
- Government - courtrooms
- Education - classrooms & lecture halls
- Entertainment - Auditoriums, Theaters
- Retail - Service Counters



View our Convey unit at [WilliamsAV.com/product/convey-video](https://www.WilliamsAV.com/product/convey-video)

## Product Specifications: Convey (TL S20)

Video Input	HDMI up to 3840 x 2160 @ 24/25/30 fps
Video Output	HDMI up to 3840 x 2160 @ 60 fps
Power Supply	TFP 060 – 100-240VAC 50/60Hz Input
Power Source	19VDC, 4.7A, center positive
Power Indicator	Green LED
Remote Power	2-pole Phoenix-style connector (Euroblock)
Network	RJ-45 LAN port for printing and saving images and third-party remote control
USB	5 USB 3.0 ports, plus one USB B-Micro port
Operating Temperature	Approximately 32° F to 122° F (0° C to 50° C)
Comm Ports	2 DB-9 Connectors supporting 9600 baud
Dimensions	1 RU – 19" (W) x 1.75" (H) x 8.2" (D) (48.26 cm x 4.45 cm x 20.8 cm)
Weight	5 lbs. (2.3 kg)
Warranty	2-year warranty against component failure and manufacturing defects. See <a href="#">Full Warranty statement on the website</a> for details.
Approvals	CE, FCC, Industry Canada, WEEE, RoHS, CBScheme, RCM, PSE