

MIC 104

Conference Microphone

Conference table condenser boundary microphone.



MIC 104

Dimensions	2.87 in x 3.56 in x 0.59 in (73.0 mm x 90.5 mm x 15.0 mm)
Weight	2.4 oz (67g)
Element	Fixed-charge back plate, permanently polarized condenser
Polar Pattern	Half-cardioid (cardioid in hemisphere above mounting surface)
Frequency Response	70-16,000 Hz
Open Circuit Sensitivity	-25 dB (56.2 mV) re 1V at 1 Pa
Impedance	100 Ω
Max. Input Sound Level	114 dB SPL, 1 kHz at 1% T.H.D.
Dynamic Range	86 dB, 1 kHz at Max SPL
Signal-To-Noise Ratio	66 dB, 1 kHz at 1 Pa
Phantom Power Requirements	9-52V, 2 mA typical
Output Connector	Bare Wire
Warranty	90 days

Domestic Sales

Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344
 Ph: 800-328-6190 / 952-943-2252
 FAX: 952-943-2174
 Email: info@williamsav.com
 Web: www.williamsav.com

International Sales

International Sales Department
 Williams AV
 10300 Valley View Rd
 Eden Prairie, MN 55344 USA
 Phone: +1 952 943 2252
 Fax: +1 952 943 2174
 Email: info@williamsav.com
 Web: www.williamsav.com